

ASDA A2

- Rated output : 1Ph/3Ph - 200V : 50W to 15.0 KW
3Ph - 400V : 400W to 15.0 KW
- Rated torque : 0.16 Nm to 95.5 Nm
- 20-bit incremental & 17-bit absolute encoder resolution
- position/ internal position/ speed and torque control modes
- 1.0 KHz velocity response frequency
- 4Mpps exclusive interface for line driver pulses
- Maximum 5000 RPM
- Maximum torque limit 300%
- Full close control with linear scale or external encoder
- Built-in electronic cam (E-CAM) function
- EtherCAT, CANopen, DMCNET communication
- Excellent solution for rotary cutter and synchronized motion applications
- CE & UL safety standard compliance
- IP 65 (except connector)



ASDA B2/B2L

- Rated Output : 1Ph/3Ph - 200V : 100W to 3.0 KW
- Rated Torque : 0.32 Nm to 19.1 Nm
- 17-bit Incremental encoder resolution
- Position/ speed and torque control modes
- 550 Hz velocity response frequency
- 4Mpps exclusive interface for line driver pulses
- Maximum 5000 RPM
- Maximum torque limit 300%
- RS-232/ RS-485 MODBUS Communication
- CE & UL safety standard compliance
- IP 65 (except connector)

